



## CONNECT PLUS MULTI-SITE DIGITAL TRUNKING SYSTEM

# MOTOTRBO™ XRT 9000 GATEWAY

Keep your workforce connected. When you fleet is dispatched across the city and your workers are miles apart, you need a way to stay connected. Scalable to meet your communication needs, Connect Plus multi-site trunking is a two-way radio system that enables your work teams to not only share voice communication, they can also use integrated data applications to make their job more efficient and safer, including text messaging, location tracking and dispatch capability. All the while, you gain the benefits of TDMA digital technology like increased capacity and clear audio.

### EXCEPTIONAL ACCESS

#### Centralized access to your workforce

Keep connected with a large workforce operating in the field by using the MOTOTRBO XRT 9000 gateway to link your MOTOTRBO Connect Plus system with an IP-based wire-line console for centralized dispatch capability.

#### Versatile performance management

Monitor, report and analyze system performance by using the MOTOTRBO XRT 9000 gateway to link your MOTOTRBO Connect Plus system with performance management applications.

### SUPERIOR CALL TRAFFIC MANAGEMENT

#### Scalable to meet your needs

Get calls through even when volume is high. From a single-site system to a 35-site system, each MOTOTRBO XRT 9000 gateway can handle up to 100 Registered Talkpaths and 30 simultaneous calls at a time. Up to five (5) XRT 9000 Gateways can be added to a Connect Plus system to provide additional capacity for the most demanding system and dispatching needs.

**PRODUCT SPEC SHEET**  
XRT 9000

**SPECIFICATIONS**

	<b>MODEL TT2386A</b>	<b>MODEL TT2395A</b>	<b>MODEL TT2394A</b>
	<b>MOTOTRBO XRT 9000 Gateway 30 simultaneous + 0 Registered Talkpaths</b>	<b>MOTOTRBO XRT 9000 Gateway 30 simultaneous + 100 Registered Talkpaths</b>	<b>MOTOTRBO XRT 9000 Gateway Adds block of 10 Registered Talkpaths (Licenses only)</b>
Performance		Celeron M, 1 GHz Microprocessor	
Ethernet Connections		4-Auto sensing 10/100/1000 Mbps Ports	
Serial Connections		8- RS232 Ports	
Operating System		Wind River Linux	
AC Input Power Requirements		100/240 VAC, 47 to 63 Hz , 50 Watts fully loaded	
Standard Warranty		Two years	

**PHYSICAL CHARACTERISTICS**

Dimensions		17.32 x 9.96 x 3.54 in (440 x 253 x 90 mm) (without mounting tabs)	
Mounting		Standard 19" rack mounting	
Weight		15.4 lbs ( 7 kg )	

**ENVIRONMENTAL**

Operating Temperature		-30 to +60°C (-22 to +142°F)	
Humidity		5 to 95% RH	
Storage Temperature		-40 to +85°C (-40 to +185°F)	

**STANDARDS**

FCC		Part 15 Subpart B, CISPR 22 Class A	
UL/cUL		UL60950-1, CSA C 22.2 No. 60950-1-03, LVD EN60950-1	

Specifications subject to change without notice. All specifications shown are typical.  
Gateway meets applicable regulatory requirements. Version 2 02/12

Motorola Solutions, Inc. 1301 E. Algonquin Road, Schaumburg, Illinois 60196 U.S.A. [motorolasolutions.com/mototrbo](http://motorolasolutions.com/mototrbo)

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2012 Motorola Solutions, Inc. All rights reserved. R3-7-2017 02/12

**MOTOTRBO™**  
DIGITAL REMASTERED.

